


DPH-270/380DL High-speed Tropical Aluminum Blister Packing Machine



High-speed Tropical Aluminum Blister Packing Machine adds forming and sealing process of tropical aluminum on the basis of DPH-270D, in order to improve the way of sealing, moisture proof, and light avoiding, to raise the value of the product. It is suitable for packing all kinds of products in pharma, healthcare industries.

Technical characters

- Fast mould change, push oriented, without using tools.
- Adopt servo traction, simple to set up, convenient to debug.
- Push oriented punch way to install the mould. It's no need to dismantle the suck nozzles if equipped with inspection and rejection system.
- Long distance between two heating plates of forming when the machine stops, to avoid PVC excessively heated and softened.
- Optional configurations include camera inspection and rejection device, mechanical hand structure with suck heads, automatic vibration guide rail feeder, etc.
- Can be equipped with servo motor and eye mark register device.

Technical Parameter

Model		DPH-270DL	DPH-380DL
punching frequency		50-105 times/min	50-105 times/min
Maximum molding area		240×260mm	360x230mm
Maximum forming depth		13mm	13mm
Traction stroke		Blanking: 20-120mm Forming: 80-250mm	Blanking: 20-120mm Forming: 80-250mm
Packaging Materials	cold aluminum	0.15-0.5 × 270mm	0.15-0.5×380mm
	Standard PVC Rigid Sheet	0.02-0.035×270mm	0.02-0.035×380mm
	Standard PTP aluminum foil	0.09-0.15×270mm	0.09-0.15×380mm
	The diameter of the reel is	70-76mm	70-76mm
Air consumption		≥30 m3/h (self-provided) Pressure: 0.6-0.8Mpa	≥30 m3/h (self-provided) Pressure: 0.6-0.8Mpa
mold cooling		Tap water or circulating water 60L/h	Tap water or circulating water 60L/h
total power		380v/50Hz 28kw	380v/50Hz 28kw
main motor		3.0KW	3.0KW
Dimensions		6550×980×1750mm	6550x1030x1750mm
Total Weight		4500Kg	5000Kg