

LT3200 Automatic Side Labeler



Automatic Side Labeler LT3200 is commonly used in food, medicine, household goods and cosmetic industries. It can paste the product composition, description, batch number and other content labels on the single side of the object, such as, cartons, bottles and flat products. This extensive labeling solution is easy to operate and shows the appearance of the texture through its perfect labeling result. Side-labeling is also the most common way of labeling, so makes it applicable in various industries. Whether it is a demand for high production capacity, or a small production in limited spaces, our automatic label applicator LT3200 can meet your needs, and able provide customize options.

Features

- 1. Standard modular design; convert into production line with the most flexible mode.
- 2. Label counter; display capacity automatically
- 3. The hand wheel with display, quickly fine-tune the best labeling position in no time
- 4. The side labeling machine can ship with the speed encoder to ensure the best labeling result.
- 5. Memory function to save parameters
- It can memorized previous parameter settings.
- 6. High level control system, keep labeling production efficient and precise.
- 7. Colored touchscreen HMI, easy to operate.
- 8. Automatically detect when there is no label take control of production at all times.
- 9. Wide conveyor belt; suitable for various product size, in turn improving machine functionality.
- 10. Low coefficient of friction (COF) guide rails: Direct the products correctly and keep the appearance intact while conveying products.
- 11. The machine equips with fixed feet and movable wheels, high mobility.
- 12. Food grade conveyor: high wear resistance and stable delivery
- 13. Stainless cylindrical foot-stands design: it's steady and easy to clean without blind spot.
- 14. Humanity design makes operation more convenient
- 15. Labeling delay function:

You can fine-tune labeling time and its position

- 16. Labeling module with stepper motor: make the labeler running stably with high performance for a long time
- 17. Advanced sensors allow fast production and accurate labeling.
- 18. Adjustable label applicator: Fine-tune labeling position, angle and height to match the products
- 19. It is made of SUS# 304 stainless steel and special aluminum alloy, which is firm and durable with GMP standards.
- 20. The procedures of labeling machine maintenance and cleaning are simple and make the utility more convenient.
- 21. Different label module options

our labeling machine is available to equip different components based on the product specifications to meet accuracy and performance at the same time,

Specification

Labeling Speed	30-90 pcs/min (depending on product and label size)
Conveyor Belt Specifications	200mm (customize available)
Label size	(Length) 10-250 mm, (Width) 10-100 mm
Label Roll	Inner Diameter 75 mm, Outer Diameter 300 mm
Accuracy	± 1 mm
Power Supply	110 or 220 VAC, 50/60 Hz , single phase
Machine Size	(L) 1400mm (W)750mm (H)1500mm