

## ***i-Sleeve Pro Single-head Auto Shrink Sleeve Applicator Machine / Labeler***



This Shrink Sleeve Applicator Machine is developed for customers who need high efficiency and high speed, and also need a small footprint.

i-Sleeve Pro, it perfectly meet the customers' need with simplified footprint and high capacity.

### **Machine Features**

- Can use Ethernet communication or dry contact I/O control during production.
- Safety guards and color touch panel control system ensure unit is user friendly.
- Specially designed cutter plate does not need changing within rated specifications. If necessary, changes can be accomplished in only three minutes.
- Use PC based control for increased accuracy and speed over conventional controls.
- Servo control adopts Ethernet communication which is less susceptible to interference.

### **Innovative Features**

- Can save up to 100 sets menu.
- With optional UWI-8 Multi Label Unwinder, label changing time can be extended to increase productivity.
- Using PET 20 micron or PVC 32 micron shrink labels at substantial film cost reduction, machine can reach 350bpm within 180mm label length.
- Using PET/PVC 40 micron shrink labels, machine can reach 600bpm within 180mm label length.
- With auto speed variation insertion capability to meet conveyor requirement.
- Can be supplied with optional Bottle Lifter to produce quality packaging.

## Specification

<b>Max speed</b>	600BPM
<b>Bottle Diameters</b>	ψ25mm~ψ125mm
	(Based on the bottle dimension of specification provided by the customer)
<b>Film Material</b>	PVC /PET /OPS
<b>Film Width</b>	PVC : 0.032mm~0.07mm, PET : 0.02mm~0.06mm,OPS : 0.04mm~0.06mm
<b>Machine Size</b>	2410mm* 1377mm* 2799mm(L*W*H)
	(Dase-Sing reserves the right to modify the appearance and dimension of the machine, in order to optimize the function of the requirement)
<b>Voltage</b>	3P;220V,380V,415V,440V
	(According to customer requirement)