



HXLAF Powder Automatic Packaging Machine



Performance characteristics:

1. The machine adopts advanced full computer touch screen operation, man-machine interface, and the operation is simple and convenient. Internationally renowned brand PLC control system can automatically complete bag making, metering, filling, filling, sealing, slitting, counting, coding, and can be customized according to customer requirements.
2. Filling metering configuration servo drive motor, programmable automatic control, large torque, stable operation, accurate measurement.
3. This machine adopts advanced R&D technology to directly feed the material into the bottom of the bag to prevent the dust from passing through the molding machine to produce the sealing material.
4. Intelligent photoelectric control device to ensure that the packaging bag pattern is complete. The pull bag adopts driving stepper motor control and color mark positioning, and has stable performance, convenient adjustment and accurate detection.
5. The overall contact material parts and casing are made of 304 stainless steel, which meets the food and drug hygiene permit standards.
6. The machine has a back seal packaging form for customers to choose. The cutter can be used in one of three ways: flat knife, serrated, and dotted line.
7. The advanced design ensures that the machine is suitable for adjustment, operation and maintenance in different industries. It can be used together with various automatic metering equipment at home and abroad.

The scope of application:

The powder packaging machine is suitable for packaging and filling and filling of powder materials in food, medicine, chemical and other industries.

Packaging materials: polyester/polyethylene, polyester aluminized polyethylene, polyester aluminum foils polyethylene, paper polyethylene, nylon and other heat sealable composite materials.

Technical parameters:

| | | |
|--------------|---------------|---------------|
| 型号 | HXLAF200 | HXLAF300 |
| 制成袋长mm | 40-200 | 200-300 |
| 制成袋宽mm | 80-150 | 100-200 |
| 包装薄膜宽度mm | 180-320 | 220-420 |
| 包装容量ml | 10-500 | 100-1000 |
| 包装速度bags/min | 5-50 | 5-40 |
| 功率Kw | 1.6 | 1.8 |
| 电压V | 220 | 220 |
| 外形尺寸mm | 880x1300x2000 | 950x1350x2100 |
| 整机重量Kg | 300 | 450 |