GQCE6701

Vertical Type Carton Erector







Online Video

Application

This machine is suitable for automatic packaging lines, include carton opening, erecting, folding bottom flaps and sealing at a time.

Key Features

- Vertical type carton erector. Manually refill unopened cardboards at any time.
- Side belt driven.
- Applicable to common cartons. Used for automatic packaging lines, include carton opening, erecting, folding bottom flaps and tape sealing at a time.
- PLC controlled. Easy to alter the program.
- Controlled by touch screen (HMI / MMI).
- Easy to adjust for different carton sizes by handwheel.
- 2170 2400 2206
- Adhesive tape seat can automatically adjust for uneven cartons, which is fast, smooth and durable.
- Japanese pneumatic components.
- Safety signal and shortage alarm of cardboard storage.
- Brush wipe down makes bottom tape sealing smooth.
- Dual suction cups.
- Easy to operate.

用途

■ 本機適用於自動化包裝生產線,開箱、成型、折底蓋封箱一次完成。

特性

- 全自動立式開箱機,隨時可補充未開之紙箱。
- 兩側皮帶驅動。
- 適用於一般常見紙箱類型,配合自動化系統,開箱、成型、折底蓋封箱一次完成。
- PLC系統控制。
- HMI人機介面控制。
- 附有操作手把,手動輕鬆調整開箱紙箱尺寸。
- 貼帶座新型設計,可自動調整紙箱之不平,快速平整耐用度高。
- 採用日製氣壓元件。
- 備有安全訊號裝置及儲箱槽無料訊號裝置。
- 搭配刷片,使底部封箱膠帶更平整漂亮。
- 雙吸盤開箱機構。
- 安裝容易,操作簡單。

Machine Size	Driven	Tape Width	Feeding Direction	Carton Size
機械尺寸	傳動方式	膠帶寬度	儲箱槽方向	可開箱尺寸
L2310 × W2400 × H1800 mm Spec. subject to change without prior notice. 機台尺寸以實際製作為準	By Side Belt 兩側皮帶驅動	2" or 3"	L Type Left Hand / Right Hand 左向 / 右向	L250~500 mm W170~400 mm H90~500 mm

Tape Overlap	Working Height	Capacity	Cardboard Storage	Voltage
膠帶前後貼	工作高度	開箱速度	儲箱槽數量	電壓
L60±5 mm	650 mm	8~10 cartons/min Depend on carton's size and material. 依據紙箱之材料、尺寸而定	90~100 pcs Depend on carton's thickness. 依紙箱厚度而增減	3Φ, 220V Depend on customer's request. 可依客戶需求指定