

HB-32 Doypack Bag Packaging Machine



- Front reels loading
- Machine with reduced sizes and higher output
- Self-supported frame, clean and without holes
- Standard stainless execution
- Reel shafts expandable without toolings
- Parallel sealings
- Low inertia cams
- Low maintenance and high durability cutting device
- Remote tele assistance
- Simplex, duplex, triplex or quadruplex machine
- Continuous unwinding
- Formats memory programmed in recipes
- Net electrical configuration

Filling stations	1-2	1-2	1-2	1-2	1-2
Maximum volume (1)	500cc	250cc	100cc	50cc	-
Outside reel diameter	500mm	500mm	500mm	500mm	500mm
Core reel diameter	70-75 mm	70-75 mm	70-75 mm	70-75 mm	70-75 mm
Maximum output	100 cycles/min.	100 cycles/min.	100 cycles/min.	100 cycles/min.	100 cycles/min.
Power consumption	20 kw	21 kw	22 kw	23 kw	-
Air consumption (2)	250 l/min.	250 l/min.	250 l/min.	250 l/min.	250 l/min.
Minim.format	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60
Max.format	200 x 175	160 x 175	105 x 175	80 x 175	

(1) Depending on product, film, formats and final machine configuration.

(2) Approx. data are for guidance only.

Effytec reserve the right to modify the machines due to ongoing technical development without prior notice.

