

GOLDEN LIN

Multi-Layer & Sealed Type Vibratory Separator 4001S-15003S



This machine is ideally for sieving and separating powder, particle and slurry in many industries, such as ceramics, food processing, pharmaceuticals, chemicals, bio-chemicals, electronics, sintering, plastic, rubber, grinding, recycle and etc.

Features:

1. Compact, lightweight, mobility, low noise and pollution, less energy consumption, and easy installation.
 2. The machine outlet can be connected to any direction. Sieved material can be discharged straight away, suitable for automated operation.
 3. No blockage on screen, high efficiency, applicable for 400 mesh or finer.
 4. Unique screen design, quick for changing screens which takes only 3-5 minutes.
 5. Easy to clean.
- Easy operation and maintenance. It can be used for single deck or multi decks.
6. All the surfaces touch with raw materials are made by stainless steel to ensure a hygienic operation.

Specifications:

Model	Capacity	Motor	Voltage	Frequency	Speed	Effective dia.	Machine Dimension	No. of Desk	Weight
	Kg/Hour	HP	(V)	(Hz)	RPM	of Screen			(kgs)
440-1S	120	3/4	380	50	1440	358mm	L510*W510*H707mm	1	90
440-2S							L510*W510*H8	2	98

							27mm		
440-3S							L510*W510*H9 48mm	3	106
600-1S							L600*W600*H8 53mm	1	105
600-2S	180	1	380	50	1400	525mm	L600*W600*H9 80mm	2	150
600-3S							L600*W600*H1 120mm	3	165
800-1S							L800*W800*H8 54mm	1	200
800-2S	210	1	380	50	1440	730mm	L800*W800*H9 87mm	2	225
800-3S							L800*W800*H1 127mm	3	250
1000-1S							L1000*W1000* H920mm	1	235
1000-2S	300	2	380	50	1440	900mm	L1000*W1000* H1060mm	2	265
1000-3S							L1000*W1000* H1196mm	3	295
1200-1S							L1200*W1200* H1037mm	1	340
1200-2S	350	2.5	380	50	1440	1000mm	L1200*W1200* H1197mm	2	365
1200-3S							L1200*W1200* H1356mm	3	390
1500-1S							L1500*W1500* H1110mm	1	515
1500-2S	500	3	380	50	1440	1400mm	L1500*W1500* H1285mm	2	
1500-3S							L1500*W1500* H1461mm	3	900 kgs