

ZKG-50 High Efficient Dry Powder Granulator Machine



Rolling compactor is a new type of pharmaceutical equipment developed in recent years in the world. It is widely used in pharmaceutical, chemical, food and other industrial production. The raw material is directly dried and dry extruded into granules using only the crystallization water of the material itself. It not only simplifies the process but also improves the quality of the product. At present, the models produced internationally can be basically divided into two types: high pre-compaction type and low pre-compaction type. In terms of appearance, it can be divided into closed and open types. In terms of yield, it ranges from 5 kg per hour to 100 kg per hour. What we introduce here is our company's third generation product Rolling Compactor-100. It is a high pre-compaction type and a closed general-purpose machine applicable for pharmaceutical production and chemical and food industries.

Advantages

1. This machine is new equipment that uses the crystal water in the material to make the powder into granules directly.
2. No wetting agents (water or alcohol) needed, to avoid the instability of the produced granules.
3. Saving procedures (wetting, kneading and drying), with high efficiency.
4. Pre-pressing is applied by compression forming, so that high density, uniform weight, and no tablet breakage can be obtained.
5. Small size, easy to be cleaned, GMP requirements can be met.
6. Granule pelletizing after sheet extrusion.
7. Avoid pollution problems such as drainage and air pollution. Uniform granularity, high efficiency and high rotate speed.
8. Wide speed range, multiple uses. It can deal with gummy and greased materials of strong viscosity, high heat sensitivity, poor mobility and high humidity. It also has the advantages of a wide range of granulating mesh.

Technical parameters

Model	ZKG-50
Max Production Capacity	10-40KG/h
	(will be different according to different material characteristics)
Granule Specification	20-80mesh
Maxium Thrust	10-20T
Pinch Roller Size	φ150*65
Pinch Roller Rotating Speed	0-20rpm
Feeding Speed	0-24rpm
Crushing Granulation Speed	60-180rpm
Highest Working Oil Pressure	15MPa
Feeding Motor Power	0.75KW
Pinch Roller Motor Power	3.7KW
Crushing Granulation Motor Power	1.1KW
Total Power	380V 6KW
Overall Dimension (L*W*H)	1160*1000*1750mm
Weight (KG)	500KG