

CVC 220 Top & Bottom Labeling Machine



- *Conveyor*
 - Encoder synchronizes all speeds
 - *ConveyorSpeed*
 - Variable speed adjustment
 - *Label Sensor*
 - No operator adjustment is necessary.
 - SelfSet™ automatically adjusts the label sensor.
 - *Product Sensor*
 - No repositioning adjustment is necessary.
-
- Self Set Auto Adjusting Control System
 - Stainless Steel Frame on lockable casters
 - Stainless Steel flat bed conveyor, 6" wide endless green belt
 - 25-Key Hand Held Terminal with LCD Display
 - Label head with up to $\pm 1/32$ " accuracy
 - Label Sensor for Paper or Opaque Labels
 - Capacity: up to 150 bottles per minute (BPM)
 - ISO 9001:2000 Certified

Labeling Speed Chart

Product Length	Label Length	Max. Capacity (BPM)	Max. Capacity (with C60 hot stamper) (BPM)
2" (50mm)	1 ⁵ / ₈ " (41mm)	200	180
4 ¹ / ₄ " (110mm)	2 ⁹ / ₁₆ " (65mm)	160	160
8 ⁵ / ₈ " (220mm)	6 ¹ / ₂ " (165mm)	60	60

Maximum Label Width (A-E designations)

A	$\frac{5}{8}$ " - 3 $\frac{1}{8}$ " (15-80mm)
B	$\frac{5}{8}$ " - 4 $\frac{3}{4}$ " (15-120mm)
C	$\frac{5}{8}$ " - 6" (15-150mm)
D	-
E	-

Technical Data

Label Length	$\frac{5}{8}$ " - 10" (15-255mm)
Product Width	1" - 6" (25-150mm)
Product Height	2" - 15 $\frac{3}{4}$ " (50-400mm)
Roll Inner Core (dia.)	3" (73.5mm)
Roll Outer Diameter	14" (355.6mm)
Power Source	110V / 220V
	50/60Hz - 1 phase
Power Consumption (Amps)	4.4

Machine Dimensions

L	1430mm
W	710mm
H*	1510mm

Conveyor

L	1430mm
W	150mm

CVC 200 Top Labeler



- *Control*
 - System SelfSet™ Microprocessor Control
- *Conveyor*
 - With encoder
- *ConveyorSpeed*
 - 0 - 32 Meters per minute, variable speed adjustment. No adjustment needed for label placement when conveyor speed is changed.
- *Label Sensor*
 - No adjustment for different label length is necessary.
 - The SelfSet™ microprocessor automatically detects the label and adjusts the label sensor to the label.
- *Product Sensor*
 - No repositioning of product sensor or timing adjustment is necessary when changing bottle size.