

HF-2800M High Quality Shrink Sleeve Steam Tunnel Machine



High quality shrink sleeve steam tunnel machine used for high speed production line or some special bottles.

- 1) Superb shrink finish with filled or cold bottles
- 2) Windows are installed inside of tunnel's body with water leaking holes, no water getting out.
- 3) Steam tubes are made of SS316 with rubber wrapping.
- 4) Low running cost, 50~60kg steam/0.3~0.4Mpa.
- 5) 6 Steam spray tubes are adjustable for complex shapes of bottles.
- 6) Exhausting blower is on the top of tunnel, its speed is adjustable.
- 7) Simple manual adjustment, and completed control.
- 8) Precise steam control by 3 digital handles for 3 areas, and saving steam.
- 9) Cancel outer water collection tray, sealed. Can be used for high speed applications.
- 10) Full body of tunnel is made of SS304 stainless steel
- 11) Strong and easy Operational handles on windows.
- 12) Steam tubes are hided under tunnel, simple and generous
- 13) Water outlet/water collection tray to avoid getting ground wet.

Parameters:

Models	HF-2800M/G
Length of tunnel	2.8meters
Main material	SS304
Braided steam soft tubes	304/316
Blower powder	Ø12, 0.25KW
Running pressure	Max 0.6Mpa
Weight	250kg
Steam consumption	50~65kg/h
Powder supply of blower	110~240V
Entrance /exit height	Max 350mm
Entrance /exit width	130~210mm
Outline size (L*W*H, m)	2.8*W0.45*1.8