

ATM-420C Automatic Grains Packaging Machine



AUTOMPACK's mission is to keep developing intelligent vertical packaging machines and offer full automatic packaging solutions. till nowadays, we already have successfully developed over 25 types packaging machine included in pillow bag/gusset bag/quad seal bag/3 or 4 sides sealing bag, connected strip bag form fill seal bagger, a these equipment able to pack all different kinds of material such as most daily snacks, food, liquid, paste, Powder etc. forming and metal spares, high technical material, vegetable, etc. cover agriculture, industrial, manufacturing all sorts fields material and commodities to pack favorable through our vertical packing machine.

Technical Characteristics:

- It is controlled by a microcomputer, with touching the screen, and the operation is simple.
- PLC computer system, function is more stable, adjust it with any parameters, and don't need to stop machine.
- It can stock ten dispose, simple to change variety.
- Sever motor drawing film, position accurately.
- Temperature independent control system, precision degree get to $\pm 1^{\circ}\text{C}$.
- Horizontal, vertical temperature control, suitable for various of mix film, PE film packing material.
- Packing type diversification, pillow sealing, standing type, punching etc.
- Bag-making, sealing, packing, print date in one operation.
- Work circumstance quiet, low noise.

Application:

- Suitable for many kinds of loose products; such as rice, popcorn, pea, Sugar and salt etc.
- Measuring range: 100-1200ML (By changing forming tube and Cups).

Technical Parameters:

Model	ATM-420C
Packing speed (bags/min)	5-60 bags/min
Max width of packing film (mm)	140mm-420mm
Packing pouch size(mm)	(L): 50-300mm (W): 50-200mm
Total power (kw)	2.2kw
Filling range(ml)	150-1000ml
Air consumption	0.8Mps 0.3m ³ /min
Type of bag making	Pillow bag/gusset bag
Max outside diameter of rolling film (mm)	≤φ400
Packing film thickness(mm)	0.05-0.12
Gross weight(kg)	600Kgs
Machine dimension(mm)	(L)1315×(W)1023×(H)1343mm
Working voltage	220v 50hz
Packing material applications	OPP, PE, PVC, OPP/OPP, OPP/PE, PET/VMPET/PE