

## *KL-400B/KL-400D Rotary Pillow Packing Machine*



### **Main performance and structure features**

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. Human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

### **Application**

Suitable for packing regular objects such as biscuit, bread, instant noodle, moon cakes, industrial parts, paper box or trays.

## Specification

Type	KL-400B	KL-400D
Film width	Max. 400mm	
Bag length	130-320mm	180-400mm
Bag width	50-185mm	
Product height	Max.40mm	Max.80mm
Film roll	Max. 320mm	
Packaging rate	30-180 bag/min	
Power	220V,50/60HZ,2.6KVA	
Machine size	(L)4020X(W)800X(H)1450mm	
Machine quality	700kg	
Remarks	Optional Air filling device	