

KSFZ-60A Tube Filling and Sealing Machine

Applicable to plastic tubes, laminated tubes and metal tubes.



Parameters

1. Adopt to the maximum tube diameter:
Metal tube: 35 mm
Plastic tube and compound tube: 40mm
2. The maximum volume: 1-150ml
3. Produce speed: 30-60 tube/min
4. Filling precision: $\leq \pm 1\%$
5. The power of machine: 1.1 kw
6. Air Pressure: 0.4-0.6Mpa

Function

Outer-heating type

1. Tube can load into station automatically and can be automatically pressed into the tube holder.
2. The automatic color mark adjusting system by stepping driving tube holder is adopted for oval tubes or other special-shaped tubes.
3. Adopt mechanical transmission mode filling system ensuring the stability of loading capacity.
4. After the sealing, the wind cooling system is adopted to prevent the heat from being conducted to the ointment.
5. PLC automatic control system.
6. Highly clear stainless steel frame.
7. The connection of emulsifier, cartoning machine and filling machine can be easily achieved.

8. It is easy to operate between different sizes of tubes.
9. Automatic completion of filling, sealing and batch No. printing in one machine.
10. Provided such functions as automatic supply of a tube to a worktable of machine, automatic tube blowing (clearing), tube color mark automatic adjustment in a holder and automatic filling and sealing.
11. Speed shall be adjustable by inverter.
12. The production capacity can be realized and control automatically.
13. The code mechanical hand print the code automatically in the request position.
14. Human-machine interface with direct display and control.
15. Tube feeding, absorbing and locating device, which is controlled by the original FESTO vacuum generator.
16. Automatic detection of tube direction inversion. Omron inversion detection phototube can accurately detect the inverted tube. (optional)
17. Automatic cleaning the inner tubes and the dust collecting system. (optional)
18. Provided with malfunction alarm, automatic stopping device when the door is opened and mechanical overload.
19. The combined material feeding forms of blow cutting and cutting can guarantee the filling of high viscosity.
20. Column style material temperature automatic control blending system.(Optional)
21. Ultrasonic hopper level sensor. (Optional)
22. USA Banner ultrasonic level probe combined with Siemens mould can be used to accurately control material level and give direct display on the touch screen.
23. No tube no fills
24. Material pump. (Optional)
25. Safe-door switching device (optional) When door opened, machine stops
26. Emergency stop button

PLC Control System

Component	Brand	Technical Parameters
Touch Screen	Siemens	7# color screen
PLC	Siemens	6ES7216
Inverter	Siemens	1.5KW
Encoder	Omron	E6B2 600P/R