

## *JNC-260B High Speed Cartoning Machine for Blister*



JNC-260B Automatic High Speed Continuous Cartoning Machine is new model which innovation design base on bringing in foreign advanced technology, also strictly according to pharmaceutical industry "GMP" standard to manufacture. With high efficiency, high performance production capacity, leaflet folding and conveying, carton opening and forming, posterior pushing structure and related technology all reach Europe and USA standards; Simple design and posterior continuous pushing structure makes operation and maintenance more convenient; three equal rotation opening carton and under twice pre-forming device to ensure that carton open and form completely.

This model is automatic high speed continuous cartoning machine which is high performance product incorporates pneumatic-photo-electro-mechanic. It suitable for automatic inserting ALU-PVC blister, bottle, soft tube, soft AL/AL strips and pouch into carton, also can link to matching machine to form production line.

### **Functions and Options**

1. No product no suck leaflet, no leaflet no suck carton.
2. Less load or no load product from magazine, machine empty run, product pushing missing, machine stop with alarm.
3. No suck leaflet continuous many times, machine automatic stop.
4. Compress air and vacuum negative pressure too low, machine stop with alarm
5. Posterior pusher make operating more convenient.
6. Quick and easy changeover product different size by hand wheel though dial plate scale.
7. Main drive with overload protection device.
8. Servo drives loading system.
9. Electrical and pneumatic components are famous international brand.
10. Automatic display speed, fault alarm and counter on touch screen.

## Technical Parameters

Item		Parameters
Steady production speed		260 boxes/min
Carton	Quality requirement	250-350g/m <sup>2</sup> 【Base on carton size】
	Dimension range (L×W×H)	(70-180) mm× (35-80) mm× (14-50) mm
Leaflet	Quality requirement	60-70g/m <sup>2</sup>
	Unfolded leaflet specification (L×W)	(80-250) mm× (90-170) mm
	Fold range (L×W)	【1-4】 Fold
Compressed air	Working pressure	≥0.6mpa
	Air consumption	约160-200L/min
Power supply		380V 50HZ
Motor power		5kw
Machine dimension (L×W×H)		4800mm×1600mm×1860mm
Machine weight		3000kg