

## MPC-LS Sleeve Shrink Labeling Machine



## **Product Description**

- 1. Full cover stainless steel host: the whole machine is waterproof and does not rust
- 2. Adjustable cutter head: original rotary cutting, imported cutter, long life
- 3. Unitary central guide column: make the label guide more stable
- 4. Synchronous bottle divider: more stable bottle delivery
- 5. Label brushing group: the precision of the sleeve label machine is more accurate
- 6. Label control electric eye frame: the original tail fin and electric eye are combined to improve the cutting accuracy of film material.
- 7. Button control box: more user-friendly operation.
- 8. Independent feeding rack: the position of the rack can be freely selected.
- 9. Adopts PLC programmable controller, servo motor, servo drive, frequency converter, and sensor, and adopts positioning module to make the sleeve label accurate, fast, and stable.
- 10. Various bottle types, such as round bottles, square bottles, flat bottles, curved bottles, cup shapes, etc.

## **Technical parameters**

Model	MPC-LS
Main Engine Size	1100mm×1300mm×2000mm
Labeling Speed	100/250/400 bottles/min (three speed model)
Voltage	3P AC380/220V
Power	3kw
Labeling Accuracy	±1mm (Depends on product characteristics, hardness and roundness)
Applicable Bottle Diameter	28mm~125mm
Applicable Label Length	30mm~250mm
Applicable Label Thickness	0.035mm~0.13mm
Air Source Pressure	15mm-320mm
Label Material	PVC, PET, OPS
Bottle Type	round, square, oval, rectangular
Weight	700KG