

## *TY-701-3000L-06 Intermittent Motion Automatic Side Sealer*



### **Applicable products**

Linear slide, drawer slide, aluminum alloy, aluminum extrusion, wood, steel, door, plate ...etc.

### **Machine features**

- Suitable for long shape product 600-3000mm.
- Air flush to extend film with smooth product entry.
- Side sealing roller position adjustable.
- Individual motor for film collection.
- Mitsubishi PLC controller.
- Omron timer for good control on sealing & cutting.
- Individual pin roller, ease adjustment for pin position & amount.
- Panasonic sensor for product entry reading.
- Cutting blade made by 1 piece for long operation durability.
- Temp. controller with PID function and driven by SSR for stable heating performance.
- Auto alarm warning on sealing device.
- Product entry width with quick adjustment without hand tool.
- Please refer to shrink tunnel for shrinking function.
- 5-6 kg/cm<sup>2</sup> filter air is provided by buyer.

## Specifications

<b>Model</b>	<b>TY-701-3000L</b>
Machine(mm) L x W x H	4500 x 980 x 1580mm
Package Range L x W x H	L:600-3000mm
	W:50-200mm
	H:20-120mm
Speed	1-15 pack/min.
Air consumption	100L/min.
Power	220V/60Hz/1ph (upon request)
Power consumption	2.6KW
Optional Function:	
Anti-cut protection, 3 in 1 blade(PE film), stainless steel frame, product input related belt...etc., other requirement available upon request.	
*Other package size available upon request.	
*Package speed will be differ from product size, film and operator.	
*One option on max. product L, W or H while package.	