

Automatic Sleeve Sealing & Shrink Packing Machine BMD-800A



Application:

Big bottles in multi-row without trays such as drinking bottles, pure water bottles, beer bottles, etc. It can be connected and work with auto filling machine.

Technical parameter:

SEALING TYPE	SLEEVE SEALING
POWER SUPPLY	380V/50-60HZ/3PHASE
MAX PRODUCT SIZE	420(L) X 300(W) X 300(H) MM
MAX PACKING CAPACITY	18 PACKS PER MINUTE
FILM TYPE	POLYETHYLENE (PE) FILM
MAX FILM SIZE	600 (WIDTH) X 280MM(OUTER DIAMETER)
POWER CONSUMPTION	MAX. 20KW
TUNNEL OVEN SIZE	1800MM(L) X 600(W) X 400(H) MM
TUNNEL CONVEYOR SPEED	VARIABLE, CONTROLLED BY FREQUENCY CONVERTER
TUNNEL CONVEYOR	CHAINS WITH SILICON COATED RODS OR STEEL MESH CONVEYOR
WORKING HEIGHT	850-900MM
AIR PRESSURE	0.5MPA (5 BAR)
SEALING KNIFE	DURABLE "U" SHAPE ALLOYED SEALING KNIFE AND SAW TEETH CUTTING KNIFE WITH ANTI-STICK TEFLON COATS
OPERATION PANEL	SIEMENS COLORFUL TOUCH SCREEN, OMRON TEMPERATURE CONTROLLER
MACHINE MATERIAL	CARBON STEEL
MACHINE WEIGHT	1050KG
MACHINE DIMENSIONS	4260 X 2400 X 1670MM

Layout:

