

MULTIMAC-C & PE-C series

Sleeve wrappers with 90° feeding system

Features:

- Two single wound films are placed on to the upper and lower side film carriage rollers
- Top and bottom motorized film drive and relevant film advance balancer attachments
- 90° Infeed belt for automatic infeed
- Advantage of making group sets with the benefit of 90° infeed belt
- Photo eye control for package infeed
- Pneumatic pusher with side guides for package infeed
- Automatic discharge belt until heat tunnel
- Constant sealer to give two seals with a center cut fitted with a cartridge heater
- Digital temperature controller for consistent seal with a thermocouple control
- Pneumatic cylinder and double heavy duty linear bearings for accurate motion
- Easy to change rubber and Teflon set on the bottom jaw
- PLC programmed software for customized inquiries and flexibility
- Detection sensor against package or hand entrapment
- Optional holder to keep the package steady during sealing by soft vertical cylinder
- Max. height adjustment for the jaw
- ISO 9001 quality standard with the relevant norm's confirmations
- CE marking
- Manufacturer's guarantee for spare part stock and after sales support.
- One year warranty on non-wearable parts



MULTIMAC-C & PE-C series

Sleeve wrappers with 90° feeding system



Models	Dimensions AxBxCxDxExFxH (mm)	Infeed belt width (mm) (B)	Seal-bar Length (mm)	Air supply (per cycle)	Max. film width (mm)	Power supply 400v, 3ph	Consumption (Max/Avg)	Capacity	Weight Net/ Crated
PE80-C Code :Y12 098 0232	1710x455x 1530x960x 1070x600x1840	255 or 455	800	6 bar 10dm ³ 608m ³	900	4 amper	2,2 / 1,2 kW	10-15 packs/min	196/285kg
PE120-C Code :Y12 098 0302	1710x450x 1885x960x 1470x1000x1840	255 or 455	800		1300	6 amper	3,0 / 1,5 kW		235/375kg
PE150-C Code :Y12 098 ****	1710x455x 2185x960x 1770x1200x1840	255 or 455	800		1600	7 amper	3,5 / 1,8 kW		286/465kg
MULTIMAC60-C Code :Y12 098 0232	3350x455x1530x960x 870x450x1840mm 32x18x60x38x35x18x72	255 or 455	600		700	44 amper	13,2 / 7,5 kW		560/620kg 1235/1367lb
MULTIMAC80-C Code :Y12 098 0302	3350x455x1530x960x 1070x600x1840 mm 32x18x60x38x42x24x72	255 or 455	800		900	46 amper	17,2 / 8,5 kW		645/728kg 1422/1605lb

*Color: Metallic dark gray (RAL code : custom color)

Warranty: One year on non-wearable parts

