ES AQUA LTD

Automatic Sticker Labeling Machine ES-308A



Features:

- 1. Suitable for labeling labels made of material like OPP, paper-plastic composite film, paper label etc in the industry of detergent, beverages, mineral water, food etc.
- 2. Apply to label different shape of bottles like round, square or oval.
- 3. Full-automatic high speed labeling procedures instead of inefficiency labeling way by workers, enhancing the producing efficiency thereby increasing the competitiveness of products.
- 4. Adopts for OPP etc material of new type environmental materials, maximum limit low down the producing cost, save more than 30%, at the same time, using environmental materials is a development trend in the packing industry.
- 5. Adopts for advanced gluing technology, combining the features of environmental hot-melt glue, get the perfect gluing labeling effect; only gluing on the head and the tail of the label, max reducing the usage of glue, save cost;
- 6. Because of using un-contractile material of label, there is no transformation for the printing pattern on label after labeling, guarantee the packing aesthetics.
- 7. No need the high energy consuming equipments such as heat shrinkage stove etc, thereby save the energy.

Main performance

- 1. Humanization touch screen, simple operation, with on-line help function
- 2. Using GERMAN high-speed servomotor and controller for label feeding system to make sure high-speed of accuracy and stable label cutting and feeding

- 3. The main motor adopts for ultra power imported motor, guarantee stability and operation for the running of machine
- 4. Use GERMAN color code detection electric sensor, raise precise of label feeding
- 5. Perfect tuning protection system can realize the alarm of stop such as lack of label; omit labeling, bottle jam, temperature inspection, lack of air source
- 6. The rotary type of mold position labeling way can make sure the accuracy and stability of label sealing
- 7. Adopts for SIEMENS etc imported world famous electric components guaranteeing the Reserve online interface function, conveniently for connecting with other equipments

Overall process:

Bottles feeding in \rightarrow pre-position \rightarrow cutting label \rightarrow gluing \rightarrow label steady \rightarrow pressing \rightarrow finished

Power	380V 50HZ	Labeling glue	Hot melt
	8000W		
Machine	3000*1800 mm	Gluing temperature	120-160°C
dimensions			
Method of speed	Uninterrupted	Type of label	OPP label
adjustment	adjust rate		paper label
			paper-plasti
			composite
			film label
Max speed of labels feed	Maximum speed	Vessel diameter	40-100mm
	of 100m/min		
Labeling precision	±1mm	Labeling stations	16 per-cycle
maximum width	500mm	Max labeling speed	18000PCS/H
maximum diameter	600mm	Machine weight	1500KG
Paper core diameter	152mm		