



Main Data

Output

- Max. 1000 pcs/min
- Max. 100 sticks/min

Size Range

- Length: 15-20 mm
- Width: 12-25 mm
- Height: 8-12 mm

Connected Load

- 16.9 kw

Utilities

- Recycling cooling water consumption: 5 l/min
- Water temperature: 10-15°C
- Water pressure: 0.2 MPa
- Compressed air consumption: 5 l/min
- Compressed air pressure: 0.4-0.7 MPa

Wrapping Materials

- Wax paper
- Aluminum paper

Wrapping Material Dimensions

- Reel diameter: 330 mm
- Core diameter: 76 mm

Machine Measurements

- Length: 2300 mm
- Width: 2890 mm
- Height: 2150 mm

Machine Weight

- 5600 kg

Special Features

- Programmable motion controller, HMI and integrated control
- Automatic splicer
- Servo motor driven assists wrapping paper pulling, feeding, cutting and positioned wrapping
- No candy no paper, automatic stop when candy jam appears, automatic stop when wrapping materials run out
- No candy no paper, automatic stop when candy jam appears, automatic stop when wrapping materials run out
- Intelligent candy feeding aligning and mechanical candy pushing
- Pneumatic automatic core locking of wrapping materials
- Pneumatic knife support lifting
- Modular design and easy to dismantle and clean
- CE safety authorized
- Protection standard: IP65

BZT1000

STICK PACK MACHINE IN FIN-SEAL

BZT1000 is an excellent high-speed wrapping solution for rectangle, round shaped candies and other preformed products in single fold wrapping and then fin-seal stick packing

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road, Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

We reserve the right to change any or all specifications without prior notice

