



GH-6030AF&SF-15040E Multi Packing Machine Shrink Wrap



GH-6030AF Fully-auto Horizontal Double Side Sealer which is developed for special big items adopts advanced high speed double-side sealing technology. It has up & down single film rollers. The film is in sync with the items. While the items are going forward, the side sealing system starts to seal and cut the up & down film that keeps good sealing;

Continuous sealing & cutting and no limits of the item length make it particularly suitable for longer, wider and heavy products 'fully-closed packaging with PE film, such as doors, ladders, furniture, mattresses and other heavy and oversized objects;

The waste film can be winded automatically for easily clean-up;

Side sealing lines can be adjusted to the desired position which based on the product's height in order to achieve excellent sealing strength results;

For 0.04 ~ 0.18mm thickness PE shrink film;

Input & output conveyors and colored film positioning function can be added as per customer demand;

Humanized touch smart operation interface is convenient for the operator to use;

Siemens PLC program controller achieves the integrations of mechanism, electricity and pneumatic;

Imported photo sensors to detect the horizontal and vertical section to satisfy different products' packaging;

Assorted shrink tunnel SF-15040E uses imported double air circulation motors, so that the hot air in the oven can spread more evenly to get a good shrink effect;

PE high strength film is suitable for long distance transportation and frequent handling that can avoid damage and keep away from moisture

Technical information:

Model	GH-6030AF	SF-15040E
Power	6kw	30kw
Power supply	AC 380/220V 3PH 50/60Hz	AC 380/220V 3PH 50/60Hz
Max. Packing Size L×W×H	300mm≤W+H≤1250mm, L(unlimited); H≤250mm	2500×1000×250mm
Tunnel Size L×W×H	/	4000×1500×400mm
Horizontal Blade Length	1300mm	/
Air Temperature	300°C	300°C
Table Height	825±25mm	825±25mm
Packing Speed	15m/min.	0~18m/min.
Extra Air Source	6-8kg/cm ²	/
Shrink Film	PE	PE
Machine Size L×W×H	2455×1950×1960mm	5000×1850×1850mm
Packing Size L×W×H	2505×2000×2110mm	5050×1900×2000mm
G./N. Weight	1600/1500kgs	2500/2400kgs