

ATM-420D Multifunctional Corn Flour Wheat Flour Packing Machine



AUTOMPACK's mission is to keep developing intelligent vertical packaging machines and offer full automatic packaging solutions. Till nowadays, we already have successfully developed over 25 types packaging machine included in pillow bag/gusset bag/quad seal bag/3 or 4 sides sealing bag, connected strip bag form fill seal bagger, a these equipment able to pack all different kinds of material such as most daily snacks, food, liquid, paste, Powder etc. forming and metal spares, high technical material, vegetable, etc. cover agriculture, industrial, manufacturing all sorts fields material and commodities to pack favorable through our vertical packing machine.

Technical Characteristics:

- It is controlled by a micro-computer, with touching the screen, and the operation is simple.
- PLC computer system, function is more stable, adjust it with any parameters, and don't need to stop machine.
- It can stock ten dispose, simple to change variety.
- Sever motor drawing film, position accurately.
- Temperature independent control system, precision degree get to $\pm 1^{\circ}\text{C}$.
- Horizontal, vertical temperature control, suitable for various of mix film, PE film packing material.
- Packing type diversification, pillow sealing, standing type, punching etc.
- Bag-making, sealing, packing, print date in one operation.
- Work circumstance quiet, low noise.

Application:

➤ Suitable For Automatic Packaging Of Various Kinds Of Powder: Milk, Coffee, Chili Powder, Spices, Sugar, Soap Powder, Curry Powder, Washing Powder etc.

➤ Measuring range: 50g-2kg (By changing forming tube and auger filler).

Model No.	ATM-420D
Packing speed (bags/min)	5-60bags/min
Max width of packing film (mm)	140mm-420mm
Packing pouch size(mm)	(L): 50-300mm (W): 50-200mm
Total power (kw)	2.2kw
Filling range(ml)	150-1000ml
Air consumption	0.8Mps 0.3m ³ /min
Type of bag making	Pillow bag/gusset bag
Max outside diameter of rolling film (mm)	≤φ400
Packing film thickness(mm)	0.05-0.12
Gross weight(kg)	600Kgs
Machine dimension(mm)	(L)1315×(W)1023×(H)1343mm
Working voltage	220v 50hz
Packing material applications	OPP, PE, PVC, OPP/OPP, OPP/PE, PET/VMPET/PE