



TD-200SCR

Box-Motion Auto Packaging Machine



- > Adjustable cutting position and in-feed position
- > Three sets of Servo Drive System
- > 7" Color Touch Screen Panel
- > Germany SICK Photo-cell Sensor

SPECIFICATION

Machine Size	Length (cm)	292(4.5feet) 352(6feet)	Width (cm)	97	Height (cm)	141 (Without date coder) 170(With date coder)
Machine Weight	Net Weight (N.W.Kg)	575	Gross Weight (G.W.Kg)	725		
Electrical Specification	Voltage (V)	220V 3 Phase				
	Frequency(HZ)	50/60		Electric Heater (KW)	1.6KW 220V	
	Servo Motor	400W 200VAC x2 750W 220VAC x1		Control System	Colorful HMI Controlled By PLC	
	Safety Device	Emergency Stop Button				
Packaging Specification	Sealing Mode	Sealing With Heated Wheel And Straight Bar End Seal				
	Sealing Structure	Box-Motion End Seal Bars 150mm width				
	Sealing style	Former, Controls Film& Heater Melt				
	Feeding Method	Feeding Conveyor with Pusher	Discharge Method	Belt Conveyor		
	Sealing Sides	Center-Sealing + End-Sealing				
	Packing Speed (Bags/Min)	25-80 PPM, According to the bag length, feeding speed and film material				
	Max. Width of Packing Material(mm)	400				
	Min. and Max. Length of Packing Size (mm)	40 -150				
Min. and Max. Width of Packing Size (mm)	15 -100					
Min. and Max. Height of Packing Size (mm)	3 - 70					

TAI DRAGON MACHINERY CO.,LTD.

TEL +886-4-2339-8536

ADD No. 292, Fengzheng Rd., Wufeng District, Taichung City 41357, Taiwan(R.O.C.)

FAX +886-4-2333-1933

MAIL service@taidragon.com

www.taidragon.com

