

Automatic Shrink Wrapping Machines



We are an illustrious organization that is involved in manufacturing, supplying and exporting an extensive assortment of Automatic Shrink Wrapping Machines. In the manufacturing process, over backed heat resistant power coated used. Our range consists of a silicone coated stainless steel conveyor roller. Also, these come with a heavy duty turbo blower that helps in effective and efficient circulation of hot air.

Features:

- Double reel automatic shrink wrapping system for the bundling of any kind of cylindrical, rectangular and irregular shaped products
- Automatic conveying of packs can be provided on LHS -/- RHS
- Product feeding manually arranged on the loading table with push button for the starting of the automatic cycle
- Space saving sleeve
- Pneumatic pusher for automatic intake of packs
- Individual sealing bar with twin sealing elements
- Endless PVC or S.S. slate chain conveyor
- Auto temperature control
- Full heavy duty power coated tunnel covers and electric panel board
- Lading and cooling zone provided as standard feature as outlet

Product Details:

Machine weight	420 kg
Power supply	380 V
Compressed air consumption	0, 5 NI/Cycle
Compressed air pressure	6 bar
Output	Up to 1700 pcs/h
Maximum Power Required	1.5 KW
Working Plate Height (On stand)	780 mm
Minimum sealing dimension	L 90 x W 90 mm
Maximum sealing dimension	L 550 x W 420 mm
Maximum Product height	150 mm
Minimum film width	200 mm
Maximum film width	400 mm