



KV-180CSG Multi-head Scale Premade Pouch Packing Machine



Features

- Easy to operate, adopt advanced PLC from Germany Siemens, mate with touch screen and electric control system, the man-machine interface is friendly.
- Frequency conversion adjusts the speed: this machine uses frequency conversion equipment, can be adjusted within the range according to the needs of reality in production.
- Automatic checking: no pouch or pouch open error, no fill, no seal. The bag can be used again, avoid wasting packing materials and raw materials.
- Safty device: machine stop at abnormal air pressure, heater disconnection alarm.
- Use the plastic bearing, don't need put on oil, less pollution.
- Use no oil vacuum pump, avoid polluting the environment in the production.
- Huff, clamp the meatus of bag when put the windpipe into it, then huff to open up the bag fully to bottom in order to avoid the material overflow from the bag if the it is not opend fully.
- The packing materials loss low, what this machine is used the preformed bag, the bag pattern is perfect and has a high quality of the sealing part, this improved the product specification.
- Product or packing bag contact parts adopt stainless steel or other materials which accord with the food hygienic requirements, guarantee hygiene and security of the food.
- With different feeders changed to pack solid, liquid, thick liquid, powder and so on.
- The packing bag suits in extensive range, suit for multi-layer compound, monolayer PE, PP and so on Preformed bag made by film and paper.

Application & Bag Type

Application: suitable for puffed food, chips, peanut melon seeds, rice seeds, monosodium glutamate, white sugar, bean, corn, biscuits and other granule solid materials packaging.

Technical Parameters:

Model	KV-180CSG
Production Speed	15-45bags/min
Material Weight	1-450g
Packaging Precision	±0.2g-3g(depending on material)
Control System	Servo Controller + Color Touch Screen
Bag Width	80mm—210mm
Bag Length	80mm - 280mm
Bag Type	standup bag, four side sealed bags, zipper bags, handbags, paper bags and other prefabricated bags
Bag Material	PP、PE、PVC、PS、EVA、PET、PVDC + PVC、OPP + Composite CPP, etc.
Power Supply	380V / 50Hz / 2.5kW
Gas Consumption	0.7m ³ /min
Machine Size	(L.W.H) 1770mm * 1300mm * 2126mm
Machine Weight	750kg
Optional Device	zipper opening device, exhaust device, coding machine , inkjet machine, profiled die cutting