

DXD-180B Full-automatic Horizontal Bag Packing Machine



The machine absorbing foreign advanced technology, using the bag first, then working process of the packaging, the machine adopts microcomputer PLC programmable control, photoelectric sensor, adopt servo motor to feeding, the filling way can use metering pump, piston cylinder, measuring cup different ways, accurate measurement, can be used in the three edge sealing and four edge-sealing aluminium film bag packaged products. This machine can be double bag small measuring packaging, can make the packaging more quickly. Equipment widely used in food, medicine, pesticide, daily chemical industry such as powder, liquid, particulate bag packaging.

Technical Parameters:

1.Capacity	Single bag:40-80 bag/min
	Double bag:80-150 bag/min
2.Volume	Single bag:200g
	Double bag:50g
3.Precision	±1.5%
4.Maximum bag	Single bag:2180 (W) ×225(H)mm
	Double bag:590 (W) ×125(H)mm
5.Minimum bag	Single bag:85 (W) ×100(H)mm
	Double bag:60 (W) ×70(H)mm
6.Maximum film-roll diameter	Φ500mm
7.Roll's interior diameter	Φ70-80mm
8.Power	4.5kw
9.Voltage	AC380V, 50/60Hz
10.Net weight	1080kg
11.Dimension	3550 (L) ×950 (W) ×2300(H)mm