



Link-5030LX Automatic PVC PE Film Carton Heat Shrink Wrap Sealing Box Machine



Link – 5030LX high-speed temperature shrink film packaging machine USES the lower wind, and the air volume is controlled by inverter adjust conveyor by frequency converter, speed stepless adjustable furnace chamber upside can open, easy to clean and maintain, through the contraction packaging machine in front of the window can see the whole process of packaging, can according to need to matching the front-end power feed line and the back-end hot wind cycle without a power storage platform Ring system, can reduce the heating time in the furnace heat cycle, heat insulation fiber material effectively reduce heat loss, workshop temperature is not affected to save a lot of electricity, energy efficiency high left and right air direction and bottom air flow can be adjusted to the basic configuration of roller conveyor belt, can be equipped with stainless steel or iron chloride according to product requirements.

- Manufactured with international advanced technology and imported parts and electrical components, the whole body is thickened;
- Application of electronic governor speed control, digital display computer intelligent temperature control, small temperature difference; Stable and reliable, low noise, long life;
- Stainless steel heating copper pipe, internal bidirectional thermal circulation air, inverter control, uniform heat, constant temperature;
- According to the product size, the size of heat shrink packaging machine can be customized non-standard;
- It can be operated independently or used with automatic packaging line;
- Shrinkable packaging machine products can be sealed, moisture-proof, anti-impact, suitable for multiple items wrapped packaging and tray packaging;

Scope of application:

Shrink film packaging machine is suitable for all kinds of CD, DVD, cosmetics, electronic products, printing, color box, greeting cards, small electrical appliances, photo albums, photo frames, picture frames and other products single packaging or combination packaging, suitable for mass production.

Technical Parameters:

Model	Link-5030LX
The power supply	3φ380V 50/60Hz
Power	16kw
Maximum sealing size	L 500 * W400 * H250
Installation dimensions	L1800 * W1000 * H1350mm
Work efficiency	2500-3500/h
The net weight	350kg