

Shrink Sleeve Applicator HLA Series



Product Range

- High Speed Shrink Sleeve Applicator
- Super Speed Shrink Sleeve Applicator
- Standard Shrink Sleeve Applicator
- Auto Cap Banding Applicator
- Economical Shrink Sleeve Applicator
- Steam Shrink Tunnel
- Electric Shrink Tunnel

Features

- Elegant appearance, compact construction, and unique modularization design.
- Rotating knife plate features optimal rigidity and smooth motion. With internal sensor, origination system is totally automatic.
- Mandrel easily positioned, providing efficient changeover.
- Equipped with HMI, providing easy operation.
- Innovative machine structure ensures excellent durability, unmatched by other brand.
- Succinct machine structure minimizes the possibility of troubles and optimizes the maintenance.
- Equipped with safety housing to prevent operator injury.
- Well-performing equipment at competitive price for value-added operation.
- Equipped with intelligent memory settlement when sleeving multiple bottle types at different speed, providing user-friendly and convenient changeover.

Specification

	Model	HLA-2150	HLA-2200	HLA-2250	HLA-2300
Machine	Dimension (L W H)	980 x 670 x 2040 mm			
	Weight	500 kg			
	Electric Power	AC - 3 Phase 220 V / 2.5 kW			
	Speed	150 BPM	200 BPM	250 BPM	300 BPM
Container	Diameter	Ø 10 - 125 mm			
	Height	Max 350 mm			
	Material	Glass, Metal, Plastic			
	Shape	Round, Oval, Square, Rectangular			
Shrink Sleeve	Material	PVC, PET, OPS, PLA			
	Thickness	0.035 - 0.08 mm			
	Inner Diameter of Sleeve Roll	5" ~ 10"			