

Automatic Shrink Sleeve Labeling Machine YQSL-250



Synchronized transmission, any change of transmission belt will be finished quickly. Compared to the type of traditional multilayer whose change and maintain need more than six hours, it's maintenance is easy and maintain is simple, so it doesn't influence production.

Unit cutter head plane design in China, which apply, to the container of $\phi 40\text{mm}$ — $\phi 70\text{mm}$.you never need to change or debug it. It also has unique light touch human-machine screen, that means, auto search original location as well as safety and convenience which is ahead of other congener products.

Single shrinking label feed plane, personal height, which is convenient to fix the label; microcomputer auto figure, which avoid enactment and adjustment .you, only need to press it lightly, the label will detect and locate automatically. The change of label is quick and convenient; besides, the cutting place is exact.

Technical Parameters:

- Host machine; AC220V, 50/60HZ, 3KW, single-phase
- Production speed: 150,000 b/h as 100mm label(The speed can be adjusted according to your requirement) The standard length of label is 300mm and the speed can be adjusted according to customer's requirements. The speed will be faster if the label is shorter.
- Diameter of bottle body : ϕ 20mm- ϕ 100mm(can be customized according to customer's requirement)
- Length of label: 100mm
- Thickness of label: 0.045mm
- Material of label : PVC、 PET、 OPS