

## *RZ8-S170B Double Bag Filling Sealing Machine*



The RZ8-S170B Double Bag Filling Sealing Machine, a state-of-the-art packaging solution engineered for high efficiency and precision. Speeds can reach up to 100 bags per minute. The RZ8-S170B Double Bag Filling Sealing Machine is capable of handling a wide range of materials and pouch types, making it ideal for various packaging needs.

Built with robust 304 stainless steel, the RZ8-S170B Double Bag Filling Sealing Machine complies with GMP hygiene standards, ensuring that every packaging operation meets the highest levels of food safety. The RZ8-S170B Double Bag Filling Sealing Machine is fully automated, featuring an advanced detection system that guarantees only properly opened pouches are filled and sealed, which helps to minimize waste. Additionally, the RZ8-S170B Double Bag Filling Sealing Machine is designed to recycle empty pouches for refilling, which significantly reduces operating costs.

The RZ8-S170B Double Bag Filling Sealing Machine is equipped with an intuitive PLC control system, making it user-friendly and easy to operate. Its dual independent controls allow for rapid switching between single and double bag functions, which simplifies maintenance and enhances operational flexibility.

Notable features of the RZ8-S170B Double Bag Filling Sealing Machine include imported plastic bearings that require no oiling, an oil-free vacuum pump that maintains a clean working environment, and a robust lubrication system that ensures extended machine durability. For those in need of an efficient, reliable, and hygienic packaging solution, the RZ8-S170B Double Bag Filling Sealing Machine is the top choice.

With its high sealing quality and advanced design, the RZ8-S170B Double Bag Filling Sealing Machine delivers reliable, efficient, and high-quality packaging, making it the perfect choice for businesses aiming to enhance their production efficiency and product presentation.

## Main Specification

Model	RZ8-S170S Double Bag Filling Sealing Machine
Bag Size	W:85-170 mm; L: 150-330 mm
Filling Range	≤ 1000 g
Packing Speed	≤ 100 bags /min (depending on products and bags materials)
Weight	3000 kg
Dimensions (L*W*H)	2320 mm*2060 mm*1650mm
Total Power	5.41 kw (Two heat seals, without vacuum pump)
Driving Power Source	380 V three-phase five line 50 HZ (other power can be customized)
Compress air requirement	≥ 0.4 m <sup>3</sup> /min (Compressed air is provided by the customer)