



Powder Packaging Machine AP- 800P



The whole system is closely controlled through servo based and electromagnetic clutch and break mechanism. Moreover, we also provide various web controller options such as pneumo hydraulic web edge controller and electronic web edge control. Due to our sophisticated machines and hard-working workforce we have been able to go beyond all the expectations of our valued clients.

Salient Features:

- Film is drawn speedily out of rolls by servo based and electromagnetic clutch and break mechanism.
- Robustness provided with steel body
- Have 4 side sealing
- Pack speedily up to 60 SPM
- Utilize electrical power up to 7 KW
- Depending on the products can pack up to 200 gram of products

Technical Specifications:

Machine speed	Up to 60 SPM depending on the product & sachet/pouch dimension.
Packing range	Suitable to pack up to 200 gram and depending upon product to be packed
No. of tracks	Up to 6 tracks depending on sachet/pouch width
Max. roll width	800 mm
Max. roll dia	350 mm
Max length of pouch	Up to 200mm
Film draw mechanism	Options
	a) Servo based
	b) Electromagnetic clutch and break
Web controller	Options
	a.) Electronic web edge control
	b) Pneumo hydraulic web edge controller
Compressed air	2CFM @ 6 kg/cm sq.
Electrical power required	Up to 7 KW
Main Body Frame	Option:- SS Body
	- MS with Powder coating.
	- MS with SS cladding
Type of Sealing	4 Side Sealing
Machine dimension	2285 mm X 1475 mm X 2100 mm
	(Height mm X Width mm X Length mm)
Net weight	2000 kg