

TY-700-80 Automatic L-Sealer



TAYI YEH TY-700-80 Auto L-Sealer is your best effective and economical choice for smart roomy facility layout. With packaging speed up to 25 PPM, TY-700-80 is a new standard of sealing automation.

Features

- Safety protection & alarm
- Integrated seal knife with curved joint for smart sealing line recondition
- Heavy duty sealing knives, no build-up & smoke whilst sealing
- Isolated perforating rod for easy adjustment without tearing line
- Easy operation & adjustment
- High efficiency to maximize capacity
- Extra pin roller guide for better film control and saving
- PLC control system alternative in standard program and timer control
- Temperature, Sealing Time, Sealing Height adjustable
- Suitable for POF & PE film

Specification

- Production capacity*: up to 25 packs per minute
- Conveyor speed: 26 meters per minute (constant speed)
- Electrical: 220 Volt, mono phase, 10 Amps, 2.2 KW
- Compressed Air requirement: 70PSI
- Machine Dimensions: 1600(L) x 810(W) x 1550(H) mm

- Package Range: 100-300(L) x 40-250(W) x 5-80(H) mm
- Sealing length (End): 380 mm
- Sealing length (Side): 400 mm
- Maximum Seal bar clearance height: 80 mm
- Elevation: 750 mm
-

* Production capacity is subject to product size, type of product, shrink film material and shrink film thickness.

** Specifications are subject to change without prior notice.

Applications

Widely adopted by general industries such as food, canned food, electronics products, toys, salted materials, metalwares, tools, cosmetics, pharmaceutical, daily essentials for shrink wrap purpose.