

Fully Auto L-Type Sealer LSA-706A



Fully Auto L-sealer, LSA-706A control system adopted PLC & HMI with counting & alerting features, easy maintenance. It has strong sealing line, which is thin & good look.

The sealing cutter is installed safety & alarm system to protect worker.

Features:

- LSA-706A control system adopted PLC & HMI with counting & alerting features, easy maintenance.
- LSA-706A adopted constant heat forged bronze sealing knife, which has long life, strong & clean seal without polluted gas.
- Total 2 set of vertical & horizontal sensors can be switched to work any shape of products perfectly, even thin & small size.
- It is easy to change packaging size on feeding belt. The quick positioning design can save changing time without needing replacement of jig or former.
- Machine is adjusted easily for size change without needing replacement of jig or former. It can also run multiple packages to help promotional purpose.
- Expanded sealing size is suitable for any kinds of products with strong seal.
- The auto wasting trim winding unit is driven by individual motor. It has 3-paw winding core, which can help wastage be taken out easily.
- Guarding cover prevent worker from inquiry by machine operation.
- It is designed by vertical sealing system.
- Auto film feeding, the sensor & timer work together to control sealing length automatically.
- The standing-by function can help reduce feeding seconds & increase producing capacity.
- Sensitive & accurate temperature controlling system of sealing knife can be setting & changing easily.
- POF is environmental friendly. It is only recommended to run with LSA-706A.

Specification:

- Power: 3Ø 220V 50/60HZ
- Machine Dimension: 2420 x 1830 x 1760 (m/m)
- Sealing Bar Length: 750 x 650
- Max. Package Height: 10 - 260 (m/m)
- Heater: 1.7 (KW)
- Motor: AC60 x 1, AC40 x 1, AC90 x 3, AC15 x 1
- Packaging Capacity: 15 (Boxes/Min) Box: 180 x 110 x 42 (m/m)
- Air Pressure Required: 5.5 (80psi) KG/cm²