



DSM-(P10) Plastic Ampoule Filling Machine (10 head)



This machine is suitable for the unit dose of medicine, drinks, dairy products, health products, food cosmetics, perfume, agricultural medicine, fruit purees, etc.

Performance and characteristics:

1. HC high speed and high precision high-end motion controller. Stepless frequency control of motor speed control .Servo motor control tensile membrane device.
2. The man-machine interface. Device, the operation is simple.
3. Automatic discharge volume, a roll of film cutting ,can be folded in half.
4. There are positive and negative photoelectric pattern of version of the function. Products elegant, meet high standards of packaging requirements.
5. Using electronic peristaltic pump device. And mechanical pump piston pump control.Adjustment is convenient. Filling accuracy is correct. Filling does not drip, no bubble, no overflow.
6. Parts in contact with the medicine with high quality stainless steel 316L, machinery casings are all SUS304 stainless steel. In line with the GMP standard.
7. At the bottom of the bottle is flat, can stand.

Technical Parameters:

Max forming depth	12mm
Cutting frequency	0-20 times
Material packaging	PVC/PE PET/PE (0.2-0.4)x240mm
Capacity	1-50ml
Power	8Kw
Voltage	380V/50Hz
Whole machine's weight	2000Kg
Outer size LxWxH (mm)	5000x850x1400(mm)