

LQ-BTB-400 Cellophane Wrapping Machine



The machine can be combined to use with other production line. This machine is widely applicable to the packaging of various single large box articles, or the collective blister pack of multi-piece box articles (with gold tear tape).

The material of the platform and the components in contact with material are made of quality hygienic grade non-toxic stainless steel (1Cr18Ni9Ti), which is completely in line with the GMP specification requirements of pharmaceutical production

To sum up, this machine is high intelligent packaging equipment integrating machine, electricity, gas and instrument. It has compact structure, beautiful appearance and super quiet.

Feature

1. The machine is pneumatic, applying the principle of the coating package, and adopts multi-function digital display frequency conversion step-less speed adjustment. PLC can be programmed to control the design technology, realize the thermo seal, automatic control of the plastic temperature, automatic feeding and automatic counting.
2. Using the servo motor to fall the film, it is equipped with the stable air pump to make the film fall smoothly and eliminate static interference.
3. Apply touch screen and other imported electrical components to realize man-machine interface operation. Can complete programming setting, control operation, tracking display, box overload automatic protection, failure stop
4. The machine is equipped with the whole process of assembling, stacking, wrapping, sealing and shaping of single package.
5. The material of the platform and the components in contact with material are made of quality hygienic grade non-toxic stainless steel (1Cr18Ni9Ti), which is completely in line with the GMP specification requirements of pharmaceutical production

6. To sum up, this machine is high intelligent packaging equipment integrating machine, electricity, gas and instrument. It has compact structure, beautiful appearance and super quiet.

Technical Parameter

Model	LQ-BTB-400 Cellophane Wrapping Machine
Packing Material	BOPP film and gold tear tape
Packing Speed	25 - 40 packs/min (Depend on box size)
Max Packing Size	(L) 300 × (W)200 × (H)100mm
Electric Supply & Power	220V, 50Hz, 5.5kw
Weight	800 kg
Overall Dimensions	(L)2400 × (W)1200 × (H)1800mm