



DPP-260H2 High-speed Al-plastic Blister Packing Machine



The machine is suitable for capsule, tablet, big honey pill, candy, liquid, paste, syringe as well as irregular shape Al-plastic, paper-plastic composite and Al-Al sealing packing in pharmacy, healthcare, food, cosmetics, medical equipment industry etc, fully comply with "GMP".

Characteristics

1. Adopts Siemens brand PLC programmable control, color touch-screen operation, frequency control speed, servo with reducer traction, traction length can be adjust freely (within parameters scope) to avoid the error that caused by artificial mechanical adjustment, significantly reduce labor intensity and material waste ;
2. Main machine overload protection, PVC and PTP packaging material position detection and alarm shutdown, automatic fault diagnosis, alarm and automatic shutdown protection ;
3. The feeder adopts air vibration feeding and hopper material position detection and control, in abundance reduce the stirring and friction order to protect the integrity of material ;
4. Each working position of the whole adopts quick-loading design, suitable for multi-product production, easier and more reliable to change mould (to change a mold just need about 30 minutes) ;
5. Adopts special processing and assembly process to ensure that AL foil is balance and do not run slating and shake, prompts the register more accurate and stable ;
6. Automatic waste winding device, easy to collect waste, orderly finished output, the output ora installed conveyor to provide the necessary conditions for the following manufacturing ;
7. One machine for two use, you can replace a small part of the structure to manufacture Aluminum-Plastic or aluminum-aluminum products ;
8. The whole machine adopts separation connection design, easy to enter into lift and workshop.

Technical Parameters

| Model | DPP-260H2 |
|---------------------|---|
| Cutting Ffrequency | Al/plastic25-60times/min |
| Production Capacity | Al/plastic : 140thousand Grains/hour |
| Max Forming Depth | Al/plastic : 22mm (customized forming depth) |
| Travel Range | 30-120 mm (made to order140 mm) |
| Total Power | 380V 50HZ 8.5KW |
| PVC Rigid Sheet | 0.25-0.5×260 mm |
| Dialysis Paper | 50-100g×260 mm |
| PTP Aluminum Foil | 0.02-0.035 ×260 mm |
| Cooling | Condensate (self) or cold circulating water(optional) |
| Overall Dimensions | 4460×760×1620mm |
| Weight | 1850kg |