

DCW-250B Horizontal Packaging Machine Series



I. Main performance and structure features

1. Dual frequency conversion control, bag length can be set and cut in one step, saving time and film.

- 2. Interface features easy and quick setting and operation.
- 3. Self failure diagnosis, clear failure display.

4. High sensitivity photoelectric eye color tracing, numerical input of cutting sealing position for extra accuracy.

5. Temperature independent PID control, more suitable for packaging different materials.

6. Positioned stop function, without sticking knife or wasting film.

7. Simple driving system, reliable working, convenient maintenance.

8. All control is realized through computer program, easy for function adjusting and technical upgrade.

II. Application

Suitable for packing regular objects such as biscuit, bread, instant noodle, moon cakes, industrial parts, paper box or trays.

III. Optional device

- 1. Code applying machine
- 2. Line sealing wheel
- 3. Moiré terminal sealing mould
- 4. Extra big screen

Specification:

Model	DCWB-250B	DCWB-250D	DCWB-250E	DCWB-250S
Film width	Max.250mm		Max.180mm	
Bag Length	65-190mm	90-220mm	50-115mm	45-90mm
	or 120-280mm			
Bag Width	30-110mm		30-80mm	
Product Height	Max.40mm	Max.55mm	Max.35mm	
Film roll Diameter	Max.320mm			
Packing Speed	40-230bag/min		60-330 bag/min	
Power Supply	220V,50/60HZ,2.4KW		220V,50/60,2.4KW	
Machine Size	(L)3770*(W)670*(H)1450mm			
Weight	About 700Kg			
Remark	Gas filling device is optional			