



ZTV-5K Automatic Rice Pillow Bag Vacuum Packaging Machine



The unit consists of ZVF-350 auto vertical packaging machine, auto weighing machine, Z type bucket elevator, vacuum packaging machine and take-off produce conveyor. the machine line advanced in material-lifting, measuring, bag-making, filling, vacuuming, sealing, cutting and conveying such chief processing step, take result in getting nice bag shape and appropriate vacuum degree.



Main performance and functional characteristics:

1. Equipped with safety protection, comply with firm's safety management requires;
2. Use intelligent temperature controlling machine to have accurate temperature control; ensure the artistic and neat seal;
3. Use PLC Servo System and pneumatic control system and super touch screen to form the drive control center; maximize the whole machine's control precision, reliability and intelligent zed level;

4. Touch screen can store the technical parameters of various kinds of products, no need to reset while products changing;
5. Have error indicating system, helping to handle the trouble immediately;
6. Make block bags and hanging bags according to customers' different requires;
7. Both stainless steel machines and carbon steel machines;
8. Single-belt transportation, placidly and quickly, small friction, little waste;
9. Have stainless steel model and carbon steel model for choose.

Technical parameters:

Model	ZTV-5K
Measuring range	1000-5000g
Measurement accuracy	5-10g
Bag Type	Pillow bag Hole Punch
Operation Mode	Intermittent
Speed	Up to 15bags/min
Bag Length	50-460mm
Bag Width	80-350mm
Reel Film Width	730mm
Film Thickness	0.04-0.12mm
Packing material outer diameter	Φ500mm
Packaging materials Neijin	Φ75mm
Voltage	AC 220V/ 50HZ, 1phase or per customer needs
Power Consumption	5KW
Compressed Air Requirement	0.6MPa, 0.36 M3 / Min
Weight	1500kg