

RCGF Juice & Tea Drink Filling Machine



Juice filling machine/tea drink filling machine/milk filling machine/hot filling machine/bottle filling machine/Tea Drink Filling Machine

Usage:

RCGF series Juice filling 3-in-1 machine is introduced advanced foreign technology such as washing, filling, capping technology. It is used in filling hot fruit juice, tea, milk and other drinks, To replace some parts, it can also be used in filling normal temperature filling.

Beverage Machinery-Equipment characteristics:

1. Using the wind sent access and move wheel in the bottle directly connected technology; canceled screw and conveyor chains, this enable the change of the bottle-shaped become easier.
2. Bottles transmission adopt clip bottleneck technology, bottle-shaped transform not need to adjust the equipment level, only change related the curved plate, wheel and nylon parts is enough..
3. The specially designed stainless steel bottle washing machine clip is solid and durable, no touch with the screw location of bottle mouth to avoid secondary pollution.
4. High-speed large gravity flow valve filling valve, filling fast, filling accurate and no liquid lose.
5. Spiraling decline when output bottle, transform bottle shape no need to adjust the height of conveyor chains.
6. Host adopt advanced PLC automatic control technology, the key electrical components from famous company such as Japan's Mitsubishi, France Schneider, OMRON.
7. Equipped with a constant temperature system, temperature controlled and circumfluenting automatically.

Technical Data:

Model	Number of washing filling and capping	Production capacity	Applicable bottle specifications (mm)	Power(kw)	Dimension(mm)
		Bottle per hour(0.5L)			
RCGF14/12/5	14, 12, 5	2000-3000	0.25L-2L	3.58	2100x1400x2500
RCGF18/18/6	18, 18, 6	4000-6000	50-108 mm	7.61	2460x1720x2650
RCGF24/24/8	24, 24, 8	6000-8000	H=170-340mm	8.2	3100x2100x2650
RCGF32/32/8	32, 32, 8	10000-12000		9.18	3500x2500x2650
RCGF40/40/10	40, 40, 10	13000-15000		10.28	4600x1800x2650
RCGF50/50/12	50, 50, 12	16000-18000		11.28	5200x4500x3400
RCGF60/60/15	60, 60, 15	20000-22000		11.28	6500x4500x3400