



TB/STB -150/250/350 Auto Film Sleeving And Shrinking Labeler



Performance:

1. The machine is made of stain-steel and high quality Aluminum alloy, striation in reason, tighten, adjustment conveniently.
2. Not need ground feet bolts, move conveniently, flexible assort production pipe field.
3. Shrink film volume label frame according different volume label paper pipe adjuated range 5"-10"

4. Transmission machine can be adjusted conveniently without tools, which make it more suitable for bottle sizes.
5. Forced insertion design proves reasonable and convenient.
6. Volume label cut of measure system ensure small error
7. Special designed knife plate is change free with the related specifications.
8. New nip system, change and installation rapidly without tools.
9. Disport bottle screw located strap transport chain adopts synchronization adjust model, adjust facility.
10. Introduce Japanese servo motor and high-delicacy photoelectricity, the length of cutting label is precision.

| 主要技术参数 Main Technical parameters | | TB-150/STB150 | TB-250/STB250 | TB-350/STB350 |
|----------------------------------|--|--|---------------------|---------------------|
| 机型 Model | | TB-150/STB150 | TB-250/STB250 | TB-350/STB350 |
| 长X宽X高(mm) Dimensions (LxWxH) | | 2400×1000×2200 | 2440×1000×2200 | 2440×1000×2200 |
| 重量 Weight | | 600kg | 600kg | 700kg |
| 电源 Electric power | | AC3-Phase 220V/380V | AC3-Phase 220V/380V | AC3-Phase 220V/380V |
| 速度 Speed | | UP to 200BPM | UP to 300BPM | UP to 400BPM |
| 高度 Hight | | MAX 320mm | MAX 320mm | MAX 320mm |
| 直径 Diameter | | φ50-φ110 | φ50-φ110 | φ50-φ110 |
| 材质 Materials | | 玻璃、金属、塑胶 GLASS, METAL PLASTIC | | |
| 形状 Shapes | | 圆、椭圆、方型、长方形 ROUND, OVAL, SQUARE, RECTANGLE | | |
| 材质 Materials | | PVC, PET, OPS, OPP | | |
| 厚度 Thickness | | 0.035-0.10mm | 0.035-0.10mm | 0.035-0.10mm |
| 标签长度 Length | | MAX 150mm | MAX 150mm | MAX 200mm |
| 标签折径 Flat width | | MAX 175mm | MAX 175mm | MAX 175mm |