

## KL-350W/450W/600W Reciprocating Pillow Packing Machine



## Main performance and structure features

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.

- 2. Touchable human-machine operation, convenient and quick parameter setting.
- 3. Self diagnosis failure function, clear failure display.

4. High sensitivity optical electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.

- 5. Separate PID control to temperature, suitable for various packing materials.
- 6. Reciprocating type sealing device, firmer sealing, no wasting in mould sealing cutter.
- 7. Terminal sealing device, more beautiful bag shape, improving products level.
- 8. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
- 9. Simple driving system, reliable working, convenient maintenance.
- 10. All the controls are achieved by software, convenient for function adjusting and upgrading.

## Application

Suitable for packing regular objects such as biscuit, bread, instant noodle, moon cakes, industrial parts, paper box or trays.

## Specification

Model	KL-350W	KL-450W	KL-600W
Film width	Max.350mm	Max.450mm	Max.600mm
Bag length	110-330mm	120~450mm	120~450mm
Bag width	30-130mm	50~160mm	50~200mm
Product height	10-60mm	10~80mm	10~80mm
Film roll diamete	Max.320mm		
Packing speed	30-120bag/min	20~75bag/min	
Power supply	220V 50/60Hz 2.4KW	220V,50/60HZ,3.2KVA	220V,50/60HZ,3.6KVA
Size(mm)	(L)3670*(W)820*(H)1410	(L)3980×(W)860×(H)1530	(L)3980×(W)970×(H)1530
Weight	650kg	960kg	1160kg