

## *Cup Sealer Automatic Filling Machine CP-6R*



### **Feature**

- This machine is applicable for packing powder or grain flakes.
- As for sealing pressure, the powerful air cylinder, Double System, has been adopted.
- Sealing is done twice and attachment/detachment of a sealing bar can be done with ease for it is a rail type.
- As the operation unit and the electric box are in the upper part of the machine, water cleaning is possible.
- Mold transport can be done in Steps and the water won't overflow even if it fills up a container.
- For accurate sealing, the seal bar has a 360-degree cushion.
- Each unit holds independent functions and has been minimized in mechanical defects.
- A flashing light is turned on 2 minutes before the film is finished. When the films are completely consumed, the machine will stop at its designated position.

### **Contents**

Grain flakes, powder, grains, liquids, sauces, other relevant products and so on

### **Packing material**

AL+PE, OPP+PE, NY+PE, Other relevant packing papers with 3 sides sealed available for thermal sealing

## Specification

Packing row	6 Row
Capacity	100~150 EA/min (on 6 row)
Date printer	Jet Printer & Others Date Printer Option
Packing size	W : 20~150 xL : 20~200mm (option)
Filling capacity	20~200g (option)
Electric Power	220/380V, 3P, 50/60Hz
Compressed Air	5~7kgf/cm <sup>2</sup> , 500ℓ/min