

Cartoning Machine YQZH-100



Suitable for the packaging of snack, bottles, vials, noodle, pillow packs, etc. The machine finished running by a series of photo-electro controller to make the machine stability and guarantee the packing quality. It includes cantons in suction and open, products put into, printing batch number, sealing or option hot-glue device. The machine can be single used or linked with Filling Machine, Blister Packing Machine, Shrink Machine, and Three Dimensional Packaging Machine to form a production chain.

Feature

- International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.
- Adopt human-machine operation system.
- Automatically displaying device for trouble, speed and finished products counting.
- Machine running without pressing if no products or incorrect position of products. And stopping automatically if incorrect position of product into carton after return or no cartons or out of leaflets continuous.
- No products not suction leaflet, no leaflet not suction carton .
- Automatic detection and rejection device for lacking blister goods and leaflets.
- Protecting automatically for overloading.
- Stable performance , operation is easy .

Technical Parameters:

Encasing speed		30-80 boxes/min
Box	Quality requirement	250-350g/m ²
	Dimension range L×W×H	(30-250)mm×(20-170)mm×(15-90)mm
	Quality requirement	60-70g/m ²
Compressed air	Working pressure	≥0.6Mpa
	Air consumption	120-160L/min
Power		380V/220V,50Hz/60Hz
Motor power		1.5kw
Machine dimension(L×W×H)		3100mm×1100mm×1850mm