

YB-LT3 Auxiliary Equipment Powder Screw Auger Elevator



YB-LT3 Auxiliary equipment powder screw Auger elevator compared with similar products on the market, it has incomparable outstanding advantages in terms of performance, quality, appearance, etc., and enjoys a good reputation in the market. Weibang summarizes the defects of past products, and continuously improves them. The specifications of YB-LT3 Auxiliary equipment powder screw Auger elevator can be customized according to your needs.

It is a free standing mobile screw elevator with an integral loading hopper. A rotating paddle inside the loading hopper loosens the hopper contents and assists the feed into the tubular screw elevator section. The screw then elevates the material and discharges it into processing or packaging machinery as required.

Screw Elevator's discharge height, hopper capacity is able to be customized that depending on different powders' density and detail requests, suitable for flour, milk powder, starch, spices, ground coffee, instant drinks etc powder products' elevating application.

Application and characteristics:

1. Adopt double motor: feeding motor and vibration motor, which are controlled independently.
2. The vibration type material box and the amplitude are adjustable. The design of the material box is independent and easy to load and unload.
3. The screw can reverse discharge and is convenient for cleaning.
4. The height of the machine depends on the overall height of the machine.

Technical parameters:

Model	YB-LT3	YB-LT5
Feeding speed	3m ³ /h	5m ³ /h
Material hopper volume	230L	260L
Power supply	3ph 4 wires, 380V, 50/60Hz	3ph 4 wires, 380V, 50/60Hz
Power	820 W	1600 W
Machine size	L1000 × W800 × H900mm	L1050 × W850 × H950mm
Machine weight	150kg	180kg