



## RM series Sleeve shrink labeling machine



Entire cover type stainless steel main engine: Causes the operator safety work, the entire machine waterproofing is not rusty.

Zoom type cutter head: The creative maneuver cut-off, the two-sided knife edges, the life is most long.

List localization type center guide pillar: The label leads delivers stably.

Minute bottle screw rod: The jar transports is not easy to rock.

The label brushes the group: Wraps the sign precision to be more accurate.

Label control electric eye frame: Originally creates the tail wing and the electric eye unifies, increases the membrane material cut-off precision.

The colored man-machine touches control the screen: Operation user-friendlier.

The stationary type supplies the material frame.

### Technical parameters

Model	RM-150	RM-250	RM-350
Capacity	100-200bpm	200-300bpm	300-400bpm
Bottle size	D:φ28-125mm H:φ50-280mm	D:φ28-125mm H:φ50-280mm	D:φ28-125mm H:φ50-280mm
Label length	30mm-260mm	30mm-260mm	30mm-260mm
Label thickness	0.03mm-0.13mm	0.03mm-0.13mm	0.03mm-0.13mm
Output	200-400pcs/min		
Power	1.5kw + 15kw	1.5kw + 15kw	5kw + 15kw
Voltage	1Φ/220V, 3Φ/220V	1Φ/220V, 3Φ/220V	1Φ/220V, 3Φ/220V
Material	aluminium alloy	aluminium alloy	aluminium alloy
Oversize	2100L*850W*2000H	2100L*850W*2000H	2100L*850W*2000H