

HSD SERIES LABORATORY MIXER



IT IS MAINLY USED IN LABORATORY SOLID PREPARATION FOR MIXING OF GRANULES AND GRANULES, GRANULES AND POWER, POWDER AND POWDER. MEANWHILE, IT IS WIDELY USED IN PHARMACEUTICAL, CHEMICAL AND FOODSTUFF INDUSTRIES.

FEATURES

- 1. MOVABLE DESIGN
- 2. DETACHABLE BIN DESIGN FOR VARIOUS BATCH SIZE APPLICATION
- 3. EFFICIENT BLENDING

ADVANTAGES

- 1. SUIT FOR R&D
- 2. HIGH EFFICIENCY MIXING
- 3. SMALL FOOTPRINT

MAIN TECHNICAL PARAMETER

| Model | | HSD5 | HSD10 | HSD15 | HSD20 | HSD25 | HSD30 |
|----------------|-----|--------|-------|-------|-------|-------|-------|
| L | | 920 | 1010 | 1010 | 1090 | 1090 | 1090 |
| W | | 570 | 650 | 650 | 700 | 700 | 700 |
| W2 | | 450 | 450 | 450 | 450 | 450 | 450 |
| н | | 1000 | 1050 | 1050 | 1050 | 1050 | 1050 |
| H1 | | 470 | 410 | 410 | 360 | 370 | 370 |
| H2 | | 980 | 980 | 980 | 980 | 980 | 980 |
| H3 | | 830 | 800 | 880 | 820 | 880 | 925 |
| DN | | 50 | 50 | 50 | 75 | 75 | 75 |
| Blending speed | rpm | 3 ~ 25 | | | | | |
| Max bin Volume | L | 5 | 10 | 15 | 20 | 25 | 30 |
| loading volume | L | 4 | 8 | 12 | 16 | 20 | 24 |
| loading weight | kg | 2.5 | 5 | 7.5 | 10 | 12.5 | 15 |
| Total power | kW | 0.25 | 0.25 | 0.25 | 0.25 | 0.55 | 0.55 |
| Total Weight | kg | 150 | 160 | 170 | 180 | 185 | 190 |