

BG Series High-Efficient Film Coating Machine



The machine is widely used to cover various tablets, pills and candy with organic film, water-soluble film, sugar film, etc. In areas such as pharmaceutical, food and biological products, etc. And it has characteristics such as good appearance. In design, high efficiency, low power consumption, small floor space, etc.

Model	BG-40 D/E	BG-80 D/E	BG-150 D/E	BG-400 D/E
Max. Capacity(kg)	40	80	150	400
Power of Main Machine(kw)	1.1	1.2	2.2	3
Speed of drum(rpm)	3-28	3-24	2-20	1-13
Weight of Main Machine(kg)	550	750	900	1650
Overall dimensions of Main machine(L×W×H)mm	118×850×1520	1390×1050×1720	1750×1320×2020	2000×1680×2590
Power of high Efficiency Filter Air Heater(kw)	1.1	1.5	2.2	3
Overall Dimensions of High Efficiency Filtering Air Heater(L×W×H)mm	810×700×1720	950×800×2080	1080×820×2500	1100×910×2500
Weight of High Efficiency Filtering Air Heater(kg)	300	350	400	450
Power of Dust Cleaning Air Exhauster(kw)	2.2	3	5.5	7.5
Overall Dimension of Dust Cleaning Air Exhauster(L×W×H)mm	730×730×1660	900×800×1900	1060×1100×2100	1140×1140×2500
Weight of Dust Cleaning Air Exhauster(kg)	300	350	500	600
Power of Steam and Electro thermal Dual-purpose Heat-insulating mixer(kw)	4	4	4	4