

Automatic Flat Labeling Machine DK-P180



Apply to all kinds of flat product labeling. (for example, paper card, self sealing bag, carton, food box, medicine box, cosmetic box, stationery, CD CD, card, electric board, all kinds of oil kettle, etc.)

Main Features:

- 1. The machine mainly uses SUS304 stainless steel and aluminum alloy (sandblasting anodizing) material.
- 2. The host is driven by advanced servo system, with high speed and high positioning accuracy.
- 3. Optoelectronic products are imported famous brands, with high stability and accurate detection.
- 4. PLC with man-machine interface control, operation is concise and clear.
- 5. The host position can be flexibly adjusted on the top, bottom, front and rear, parallelism and verticality.
- 6. The speed of conveyor belt can realize digital adjustment of touch screen.
- 7. The device can operate independently and can also be connected to the production line.

Technical Parameters:

| Machine model | DK-P180 Flat label machine |
|---------------------|---|
| Machine size | 2000(L)×700(W)×1600(H) |
| Labeling speed | 30-200 pcs/min(Depending on the size of the bottle and the length of the label) |
| Object height | 30-200mm |
| Object thickness | 20-200mm |
| Label height | 5-180mm |
| Label length | 20-300mm |
| Labeling accuracy | ±1mm(Not calculate the error of bottle and label) |
| Scollinner diameter | 76mm |
| Scollouter diameter | 350mm |
| Power supply | 220v 50/60hz 0.75Kw |
| Machine weight | 180kg |