CVC 400 Front & Back Labeler



The Unique Design of CVC Front-Back Labeler:

- Labeling speed of both heads is automatically synchronized with conveyor speed to ensure quality labeling.
- Horizontal positioning screws for labeling heads, alignment belts and separators are quickly self centering and adjustable from either side of the machine.
- Push & Press Attachment ensures smooth labeling onto round surfaces without label wrinkles or bubbles. (optional)
- Angle Adjustment of Labeling Head: This unique tilt design can be angled up to 7 degrees to conform the label surface to tapered or angled containers.

Available Options:

- Clear Label Sensor
- Hot Stamp Printer
- Ink Jet Printer
- Thermal Transfer Overprinter (TTO)
- Push & Press Attachment
- 3/4/5-Panel Labeling Stations

Labeling Speed Chart

Product Width	Label Length	Max. Capacity (BPM)	Max. Capacity (with C60 hot stamper) (BPM)
1¾" (35mm)	³¼" (19mm)	180	180
43/1 6" (106mm)	4" (100mm)	100	100
7¼" (184mm)	6 ²³ / _{3 2} " (170mm)	70	70

The product speed listed above is the maximum speed (reference). Actual labeling speed will be determined when we factory-test your products.

Maximum Label Width (A-E designations)

Α	-
В	5⁄6" - 43⁄4" (15-120mm)
С	⁵%" - 6" (15-150mm)
D	⁵⁄s" - 7" (15-180mm)
Е	%" - 8%" (15-220mm)

Technical Data

	5⁄8" - 10"
Label Length	(15-255mm)
	1¼" - 4¼"
Product Width	(30-110mm)
	1¼" - 7¾"
Product Height	(30-200mm)
Roll Inner Core (dia.)	3" (73.5mm)
Roll Outer Diameter	16" (406.4mm)
	110V / 220V
Power Source	50/60Hz - 1 phase
Power Consumption (Amps)	8

Machine Dimensions

	95¾"
L	(2430mm)
	55¼"
W	(1402mm)
	66¾"
H*	(1541mm)

Conveyor

L	95¼" (2430mm)	
W	3¼" (83mm)	

CVC 430 Front Back Labeler



CVC 430 SelfSet™ Front/Back Labeler with wrap station

LESS THAN 10 MINUTES TO CHANGE FROM WRAP TO FRONT & BACK LABELING- Simply lift off CVC's post mounted "Quick Mount TM" wrap station/plate and place 2 powered foam rubber rollers into the same mounts.