

## *Automatic Fruit Vegetable Packing Machine for Lettuce CK-ZS600*



The fruit vegetable packing machine is designed for the packaging of vegetables and fruits, and the longitudinal sealing device of the machine is on the upper part of the packaged object, which can alleviate the influence on the package when the heat sealing is performed.

The automatic vegetable packing machine is suitable for packaging products that cannot be affected by heat. Such as lettuce, potato, broccoli, salad or frozen food packaging.

### **Fruit Vegetable Packing Machine Characteristics:**

1. The main line material distribution system adopts a central integrated control system to automatically adjust the distribution according to the product feeding speed and quantity.
2. The material management unit of the vegetable packing machine controls the products in order through the servo and PLC control, enters the packaging system without damage, realizes the product transportation, sorts the queue, supplies the materials automatically, and locates accurately.
3. LCD touch screen, simple operation, user-friendly design, reduce personnel operation, improve work efficiency, automatically sort products, meet the requirements of large-scale production and packaging, and ensure the continuity and stability of production.
4. The fruit vegetable packing machine adopts frequency conversion speed regulation, microcomputer control system, PID digital display intelligent temperature controller, photoelectric detection two-way tracking system, small screen display system and circuit protection system to realize stepless speed change, automatic tracking and cutting point, accurate temperature control and high packaging precision. And the machine can make different types of bags.



Linking bag



Bag with round hole



Bag with euro hole

### Fruit Vegetable Packing Machine Composition:

- Servo motor, easier maintenance

The head sealing and film feeding parts all use the servo motor alone, the stability is better.

- Anti-bite device (PACS) (optional)

Can carefully monitor the product in the packaging bag internal position deviation, when there is an abnormal situation, can immediately stop the head sealing alone.

- Standard roll film central axis control

Easy to install film, film core can be adjusted by small button.

- Printer unit (optional)

The name and number of the producer can be printed.

Model	CK-ZS600
Film width	Max .600mm
Bag length	200-600mm
Bag width	180-280mm
Product height	Max 110mm
Packing speed	15-100bags/min
Power supply	220V,50/60 HZ ,2.8 KW
Machine size	4020*820*1320mm
Machine weight	850KG